

CAROLINA

CAROLINA BREWTECH LLC

STANDARD FEATURES:

- Butterfly valves, sample valve, PVRV, pressure gauge, thermometer
- Inner shell 304 stainless steel, thickness 3mm
- Outer shell 304 stainless steel, thickness 2mm
- Interior & exterior sanitary polished
- Sight tube & ball valves assembly
- Fully pickled and passivated
- Dish bottom
- Beer outlet/dump port
- CIP assembly
- Blow off arm
- Top/side man way
- Carb stone assembly
- Dual zone dimple glycol jackets
- RTD sensor port
- 3" insulation
- Necessary fittings and valves
- Work pressure: 30Psi
- Tested pressure: 60Psi

* 3BBL Bright Tank Only

Beer Bright Tank

Size	D	H	Full Volume
3BBL	910mm [35.8in]	≈ 1770mm [69.7in]	3.7BBL
5BBL	1110mm [43.7in]	≈ 1730mm [68.1in]	6.3BBL
7BBL	1160mm [45.7in]	≈ 1970mm [77.6in]	8.7BBL
10BBL	1260mm [49.6in]	≈ 2320mm [91.3in]	12.5BBL
15BBL	1410mm [55.5in]	≈ 2510mm [98.8in]	19.4BBL
20BBL	1560mm [61.4in]	≈ 2750mm [108.3in]	24.9BBL
30BBL	1860mm [73.2in]	≈ 2870mm [113.0in]	38.2BBL
40BBL	1910mm [75.2in]	≈ 3380mm [133.1in]	51.0BBL
50BBL	2060mm [81.1in]	≈ 3470mm [136.6in]	61.0BBL
60BBL	2060mm [81.1in]	≈ 3910mm [153.9in]	71.7BBL
90BBL	2300mm [90.6in]	≈ 4600mm [181.1in]	106.4BBL



Tel: (410) 971-8326



Email: sales@carolinabeers.com



Address: Unit 505, Curtis Business Ctr 3 - 709 East Ordinance Road, Baltimore, MD 21226

<https://www.carolinamicrobrewing.com>